| File No. | 432 | SHEET | 1/1 |
|---|---|---|---|




Recommended P.C.B. Layout(Top Side)
(PCB Board Tolerance±0.05)







Section A−A

## SPECIFICATION

Current Rating:1.0 Amp
Withstand Voltage:500V AC/DC
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Operation Temperature:−40°C~+105°C
Insulator:PA9T+30%G.F.(UL94V−0),Black
Contact:Phosphor Bronze
Gold Flash Over All,Over Nickel
RoHS Compliant

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

| DRAWING No. | APPROVED BY | CHECKED BY | DRAWING BY | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE |
|---|---|---|---|---|
| 18565 | EMILY | HZF | GAO | .X ±0.40<br>.XX ±0.25<br>.XXX ±0.15<br>ANG. ±3° |
| SCALE NONE | REV. A2 | | | UNIT mm |

| NO. | REV. | REVISIONS | CHK | DATE |
|---|---|---|---|---|
| 2 | A2 | Modify Data | HZF | 07/27/2012 |
| 1 | A1 | Modify Data | HZF | 12/06/2010 |
| 0 | A0 | NEW RELEASE | BECKY | 10/18/2005 |