



Δ	Pin	A	B	Pin	A	B
	04	2.54	5.63	44	53.34	56.43
	06	5.08	8.17	46	55.88	58.97
	08	7.62	10.71	48	58.42	61.51
	10	10.16	13.25	50	60.96	64.05
	12	12.70	15.79	52	63.50	66.59
	14	15.24	18.33	54	66.04	69.13
	16	17.78	20.87	56	68.58	71.67
	18	20.32	23.41	58	71.12	74.21
	20	22.86	25.95	60	73.66	76.75
	22	25.40	28.49	62	76.20	79.29
	24	27.94	31.03	64	78.74	81.83
	26	30.48	33.57	66	81.28	84.37
	28	33.02	36.11	68	83.82	86.91
	30	35.56	38.65	70	86.36	89.45
	32	38.10	41.19	72	88.90	91.99
	34	40.64	43.73	74	91.44	94.53
	36	43.18	46.27	76	93.98	97.07
	38	45.72	48.81	78	96.52	99.61
	40	48.26	51.35	80	99.06	102.15
	42	50.80	53.89			

4U CON 元化興業股份有限公司
4U CON TECHNOLOGY INC.

DRAWING No.

20919

SCALE	NONE
-------	------

NONE

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

CYP

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

.X	± 0.30
.XX	± 0.20
ANG.	

	UNIT mm
--	------------



	A1
---	----

	$\triangle$	AO
--	-------------	----

NO.	REV
-----	-----

Modify Data

NEW RELEASES

REVI

--	--

SE

DISCUSSION

HZF

HZF

CHK

03/20/2020

10/13/2015

DATE _____